



三偏心对夹式蝶阀 Triple Offset Wafer Butterfly Valve




Figure 3D1(2)LL5H



9D1(2)WL5H



6D1(2)WL5H



主要外形尺寸 Main Outline Dimensions

PM 1.6MPa mm

DN	L	气动			蜗轮蜗杆传动					电动				重量Kg	
		H3	Ho3	B3	H1	Ho1	B1	A1	Do1	H2	Ho2	B2	A2	WF	WL
50	43	-	-	-	266	143	160	106	50	-	-	-	-	4.5	5.5
65	46	-	-	-	290	175	160	140	63	-	-	-	-	7	7
80	49	-	-	-	320	185	160	140	63	513	265	178	180	9	9
100	56	-	-	-	342	195	160	140	63	538	282	178	180	20	11.5
125	64	-	-	-	365	209	300	140	63	560	295	178	180	23	17
150	70	-	-	-	415	243	300	140	63	605	300	178	180	29	22
200	71	695	327	275	510	263	400	150	84	749	321	235	370	40	39
250	76	750	355	275	567	295	400	150	84	803	330	235	370	50	47
300	83	955	472	378	665	342	600	200	108	880	365	235	370	68	68
350	92	1033	515	378	739	385	600	200	108	960	410	235	370	105	138
400	102	1185	595	530	825	430	600	240	152	1032	445	235	370	163	190
450	114	1270	632	530	910	469	330	144	600	1118	487	235	370	205	230
500	127	1335	665	530	990	500	370	220	600	1190	520	235	370	270	265
600	154	1642	829	680	1210	618	370	220	600	1380	625	235	370	390	437
700	165	1785	905	680	1475	746	515	279	800	1582	745	245	515	465	740
800	190	1915	970	680	1600	810	515	279	800	1713	810	245	515	570	920
900	203	-	-	-	1870	1000	515	279	800	1870	875	360	540	701	1189
1000	216	-	-	-	2000	1065	570	368	600	2000	940	360	540	800	1220
1200	254	-	-	-	2215	1170	570	378	600	2118	1060	360	540	922	1680

PM 2.5MPa mm

DN	L	气动			蜗轮蜗杆传动					电动				重量Kg	
		H3	Ho3	B3	H1	Ho1	B1	A1	Do1	H2	Ho2	B2	A2	WF	WL
50	43	-	-	-	266	143	106	50	160	-	-	-	-	6.3	6.3
65	46	-	-	-	290	175	140	63	160	-	-	-	-	9	9.2
80	49	-	-	-	513	265	63	140	160	552	265	178	180	11	11
100	56	-	-	-	538	282	63	140	300	585	290	178	180	25	15
125	64	-	-	-	560	295	63	140	300	610	305	178	180	33	17
150	70	-	-	-	605	300	63	140	400	765	315	178	180	47	22
200	71	695	327	275	749	321	84	150	400	820	304	235	370	52	39
250	76	750	355	275	803	330	84	150	600	910	336	235	370	65	47
300	83	955	472	378	880	365	108	200	600	1000	386	235	370	68	123
350	92	1033	515	378	960	410	108	200	600	1055	425	235	370	138	190
400	102	1185	595	530	1032	445	128	240	800	1108	456	235	370	190	230
450	114	1270	632	530	1118	487	330	144	600	1140	490	235	370	230	265
500	127	1335	665	530	1190	520	370	220	600	1238	552	235	370	265	390
600	154	1642	829	680	1380	625	370	220	600	1399	635	235	515	437	465
700	165	1785	905	680	1582	745	515	279	800	1611	750	245	540	570	740
800	190	1915	970	680	1713	810	515	279	800	1782	820	360	540	705	920
900	203	-	-	-	1870	875	515	279	800	1915	886	385	565	730	1189
1000	216	-	-	-	2000	940	570	368	600	2040	945	385	565	927	1220
1200	254	-	-	-	2118	1060	570	378	600	2184	1053	400	770	953	1680